

PRO6S Swaged Wire Rope

6 Outer Strands, Rotation Wire Rope

PRO6S Swaged Wire Rope is a 6x26 construction. Swaging the wire rope is designed for superior strength and abrasion resistance. It is commonly used in logging applications such as winch lines, skylines, haul backs, chokers and boom pendant ropes.

6x26WS (10+(5+5)+5+1) IWRC, Load Bearing Outer Wires 156 Fill Factor 0.72

Use of swivel is not permitted.



Diameter Inches	Weight per Foot Pounds	Grade Tensile	Bluejay Code	Minimum Strength Pounds	Minimum Strength kN
7/16	0.46	IPS	W62614AS	21,100	93.9
1/2	0.60	IPS	W62616AS	26,400	117.4
9/16	0.75	IPS	W62618AS	34,800	154.8
5/8	0.92	IPS	W62620AS	41,100	182.8
11/16	1.20	IPS	W62622AS	50,200	223.3
3/4	1.33	IPS	W62624AS	59,500	264.7
7/8	1.84	IPS	W62628AS	80,600	358.5
1	2.35	IPS	W62632AS	107,000	476.0

PRO6C Compacted Wire Rope


6 Outer Strands, Rotation Wire Rope

PRO6C Compacted Wire Rope. It is offered in 6x26 for smaller diameters and 6x31 in larger diameters for increased flexibility. Compacting the wire rope is designed for increased strength, flexibility and rope stability. It is commonly used on cranes as boom hoist ropes, winch lines, clam shell buckets, logging mainlines, anchor lines, trolley lines and trailer loaders.

6x26WS (10+(5+5)+5+1) IWRC, Load Bearing Outer Wires 156 Fill Factor 0.64

6x31WS (12+(6+6)+6+1) IWRC, Load Bearing Outer Wires 186 Fill Factor 0.64

Use of swivel is not permitted.



Diameter Inches	Weight per Foot Pounds	Grade Tensile	Bluejay Code	Minimum Strength Pounds	Minimum Strength kN
1/2	0.48	EIPS	W62616AD	30,200	134.3
9/16	0.57	EIPS	W62618AD	36,800	163.7
5/8	0.73	EIPS	W62620AD	45,000	200.2
3/4	1.03	EIPS	W63124AD	67,200	298.9
7/8	1.38	EIPS	W63128AD	90,200	401.2
1	1.90	EIPS	W62632AD	112,900	502.2
1 1/8	2.26	EIPS	W63136AD	148,000	658.4
1 1/4	2.92	EIPS	W63140AD	191,000	849.6